

RELEASE NOTES



PROJECT NAME	RELEASED BY	VERSION NUMBERS	RELEASE DATE
C2-2855	Bruce Meldrum	497	12 th March 2014

DESCRIPTION

This is the third firmware release for the unit, primarily concerned with bug fixes

This release is not an executable, as it sees us move to using the new CORIOcontrol software for firmware upgrades, which only requires a .c2 file.

TYPE	FULL RELEASE	VALID FROM	12 th March 2014
-------------	---------------------	-------------------	-----------------------------

DEFECTS RESOLVED

- Fixed issue where default audio connections were swapped for YC & CV compared to design intent
- Fixed issue where front panel buttons became unresponsive for short periods of time
- Cursor key behaviour corrected when adjusting Ethernet mask
- Fixed issue where if the front panel is locked, sending the Back button pressed command via the API allows navigation to resume
- Fixed issue where Logo flashes on briefly when loading default preset
- Fixed issue where YUV range is out by 1
- Added CEA video ID code into AV Infotext
- Fixed firmware update-over-Ethernet bug

NEW FEATURES

Bug fix release, no new features

KNOWN ISSUES

- Known compatibility issue with LM1750HD when using analog RGB (PC input on display).
- Left-Push transition may show corrupt top line.
- Occasionally the unit may not reboot successfully from an API command, a power cycle fixes this issue

INSTALLATION INSTRUCTIONS

Ensure you have CORIOcontrol Software for C2-2855 v0.5.2.0 (or greater) installed

Previous versions of CORIOcontrol Software for C2-2855 DO NOT SUPPORT FIRMWARE UPDATING

If you 'Cancel Update' part way through, your unit will be left in an unusable state, it will need a power cycle to recover and the firmware will still need re-updating by repeating this procedure (missing steps 3 & 4).

1. Launch the CORIOcontrol Software for C2-2855 v0.5.2.0
2. Connect to your unit via either Ethernet or RS-232
3. Choose the 'System' menu
4. Choose the 'Update Firmware' option
5. Choose the 'Pick Update file to use...' option
6. Navigate to, and select the new firmware file you have saved from CRMDesk to your PC
7. Click 'Open' in the dialogue box
8. Choose the 'Start Update' option
9. Once complete, the unit will restart automatically and the CORIOcontrol Software for C2-2855 will reconnect

POINTS OF CONTACT:

Product Manager
Tony McAhren

tony.mcahren@tvone.com
+1 859 282 7303 phone
+1 859 240 5151 mobile

R&D

David Reynaga

david.reynaga@tvone.com