

1T-HDMI-DVI converts HDMI compliant signals to Digital DVI format signals enabling display on digital HDTV monitors or input to DVI switcher devices. HDMI inputs are transformed to RGB Digital signals. **1T-DVI-HDMI** converts a Digital DVI signal to an HDMI compliant output allowing the viewing or switching of a DVI signal on an HDMI system.

These units are Format Converters only and no video scaling takes place. The output resolution is the same as the input. For both products, all standard HDTV and most computer resolutions are supported from 480i through 1080p and VGA through UXGA. Coaxial audio (S/PDIF) is available for superior performance and input format auto-detection is used to simplify operation. Both models are 5VDC powered and the Power Adapters are included. Locking DC Connectors are provided for security.



Key Features of 1T-HDMI-DVI and 1T-DVI-HDMI

- Excellent Video Quality via HDMI/DVI interface
- Automatic Input Format Detection
- Plug and Play for easy installation
- Coaxial Audio Support (S/PDIF)
- Operation Frequency to 165Mhz

Specifications

Video Inputs	
1T-HDMI-DVI	1x HDMI via HDMI Connector
1T-DVI-HDMI	1x DVI via DVI-I Connector
Audio Inputs	
1T-DVI-HDMI	1x SPDIF Coaxial via RCA
Video Outputs	
1T-HDMI-DVI	1x DVI via DVI-I Connector
1T-DVI-HDMI	1x HDMI via HDMI Connector
Audio Outputs	
1T-HDMI-DVI	1x SPDIF Coaxial via RCA
HD I/O Resolutions (YPbPr)	
Interlaced (50&60Hz)	480i, 576i, 1080i
Progressive (50&60Hz)	480p, 576p, 720p, 1080p
Special (24 to 30Hz)	1080p@24, 1080p@25 1080p@30
PC I/O Resolutions (RGBHV)	
VGA, SVGA, XGA	60,72,75,85 Hz
XGAi	87 Hz
SXGA	60,75,85 Hz
UXGA	60 Hz
WUXGA	60 Hz (reduced blanking)
1152x864	70,75,85 Hz

Compliance	
HDMI	Version 1.0
DVI	Rev 1.0
Mechanical	
Size (H-W-D)	30x76x105mm (1.2"x3.0"x4.1")
Weight (Net)	200 g (0.43 lbs)
Warranty	
Limited Warranty	1 Year Parts and Labor
Environmental	
Operating Temperature	0° to +50° C (+32° to +122° F)
Operating Humidity	10% to 90%, Non-condensing
Storage Temperature	-10° to +60° C (+14° to +140° F)
Storage Humidity	10% to 90%, Non-condensing
Power Requirement	
External Power Supply	5VDC@2A
Regulatory Approvals	
Converter Unit	FCC, CE, RoHS
Power Supply	UL, CUL, CE, PSE, GS, RoHS
Accessories Included	
1x Power Adapter	US, UK or Euro
1x Operations Manual	
Product Item Numbers	
	1T-HDMI-DVI, 1T-DVI-HDMI

Panel Drawings

