

# MX-5288

## 8x8 DVI Matrix Routing Switcher



### Key Features

- 8x8 Matrix DVI Signal Switching
- VGA through WUXGA Signals are Supported
- Monitor EDID Cloning Support
- Buffered Video Signal Handling
- 480p to 1080p HDTV & VGA–WUXGA Resolutions
- IR Remote Control
- RS-232 Control or Ethernet Control
- Rack Mount Kit included

### MX-5288

#### Overview

MX-5288 8x8 DVI Matrix Switcher is designed to allow distribution of eight DVI-D (w/o HDCP) sources to eight devices independently or all at the same time. All video paths are buffered to prevent cross talk and 480p through 1080p HDTV signals, plus VGA (640x480) through WUXGA (1900x1200) signals are accepted as valid inputs and outputs.

All inputs are processed at full bandwidth, using single link, 165 MHz (4.95Gbps) circuitry so as to deliver no compromise outputs on all paths. Switcher memory is employed to insure last selection recall should power be temporarily lost. RS-232, Ethernet and Infrared control supplement front panel input/output selection and a rack mount kit is included with the switcher. The MX-5288 also provides output independent, per-input EDID cloning support.

### Specifications

#### Video Input

DVI-D Video 8x via DVI-I Female Connector

#### Video Output

DVI-D Video 8x via DVI-I Female Connector

#### Performance

Maximum Resolution 480p through 1080p, VGA through WUXGA  
Supported Signals DVI-D (w/o HDCP)  
Video Processing Single Link, 165MHz, 4.95Gbps  
Device Control Method Local Front Panel, plus Remote by IR, RS-232, Ethernet

EDID Capability Standard Monitor Resolutions

#### Mechanical (H-W-D)

without Rackmount Ears 44x440x200mm (1.75" x 17" x 7.9")  
with Rackmount Ears 44x482x200mm (1.75" x 19" x 7.9")

#### Weight

MX-5288 3.27 Kg (7.2lb)

#### Warranty

Limited Warranty 1 Years Parts and Labor

#### Environmental

Operating Temperature 0° to +40° C (+32° to +104° F)  
Operating Humidity 20% to 90%, Non-condensing  
Storage Temperature -20° to +60° C (-4° to +140° F)  
Storage Humidity 20% to 90%, Non-condensing

#### Power Requirement

Internal Power Supply 100-240VAC, 50-60Hz, 60W

#### Regulatory Approvals

Switcher Unit FCC, CE, RoHS  
Power Supply UL, CUL, CE, PSE, GS, RoHS

#### Accessories Included

1x AC Power Cord US, UK or Euro  
1x IR Remote Control Infrared

1x Rack Mount Kit  
1x Operations Manual

#### Optional Accessories

Cables/ Adapters Various Types and Lengths

#### Model Number

MX-5288 8x8 DVI Matrix Routing Switcher

### Panel Drawings

