1T-SX-644

HDMI Routing Switcher

Key Features

- HDMI 1.4, HDCP 1.4 and CEC1.4 Compliant
- Deep Color 36/30/24 Bit, 1080p @50/60Hz Support
- Allows switching of 4 inputs
- 3D Television Support
- Audio Return Channel Support (ARC)
- Fast Switching of all inputs
- HDCP Repeater Support
- Supports High Resolution PC Video Inputs up to WUXGA
- Supports embedded Audio including Dolby[®] Digital TrueHD and DTS-HD
- IR Remote Control and RS-232 are standard features
- OSD (On Screen Display)



Overview

1T-SX-644 HDMI v1.4 FAST Switcher with 3D / ARC allows selection of any of 4 inputs for display on an HDMI compliant display device. This version 1.4 HDMI device supports all standard High Definition Television formats, including 12-Bit Deep Color 1080p, plus PC formats through WUXGA. It also supports embedded HD-Audio, including Dolby® TrueHD and DTS-HD. Infrared Remote Control and RS-232 Control are standard features of the product.

Specifications

Audio/Video Inputs Digital Video Audio/Video Outputs Digital Video Digital Audio General Video Bandwidth Color Depth Compliance Repeater Operation Supported Video Input Format Input Signal Types Supported Audio Embedded Audio Return Audio Support **Device Control** Available Methods

Warranty Limited Warranty 4x Type A HDMI Female

1x Type A HDMI Female 1x via Coaxial connector

2.25Gbps (Single Link) Deep Color 36/30/24 bit HDMI 1.4, HDCP 1.4 & CEC 1.4 HDCP Repeater Support

HDMI Version 1.4 HDMI (plus PC Video to WUXGA)

Dolby® Digital TrueHD and DTS-HD Audio Return Channel (ARC)

Front Panel w/OSD, IR Remote w/OSD or RS-232

1 Year Parts and Labor

Mechanical Dimensions (H-W-D)

Weight Environmental

Operating Temperature Operating Humidity Storage Temperature Storage Humidity **Power Requirement** External Power Supply **Regulatory Approvals** HDMI Switch Power Supply **Accessories Included** 1x AC Power Adapter 1x Infrared Remote Control 1x Instruction Manual **Optional Accessories** Rackmount Kit

30 x 200 x 102mm (1.2" x 7.9" x 4") 592g (1.3 lbs.)

0 to +40C (+32 to +104F) 20% to 90%, Non-condensing -10 to +60C (+14 to +140F) 20% to 90%, Non-condensing

5VDC@2.6A, twist lock connector

FCC, CE, RoHS UL, CUL, CE, PSE, GS, RoHS

US, UK and Euro

RM-230 Single/Dual



1T-SX-644 HDMI Routing Switcher

Panel Drawings



